

Qty.	Description
1	SQE 2-85  Note! Product picture may differ from actual product Product No.: 96510153 3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing. The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature. The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range. The motor is fitted with a replaceable end cover with socket. Liquid: Pumped liquid: Water Liquid temperature range: 0 .. 35 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Technical: Pump speed on which pump data are based: 10700 rpm Rated flow: 2 m³/h Rated head: 88 m Approvals: CE,PCBC,RCM,EAC,CN Rohs Exempt,Morocco,UKCA,SEPRO Curve tolerance: ISO9906:2012 3B Materials: Pump: Stainless steel EN 1.4301 AISI 304 Impeller: Composite ZYTEL 70G30 HSLR PA6.6-GF30 Motor: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Installation: Maximum operating pressure: 15 bar Pump outlet: RP1 1/4 Minimum borehole diameter: 76 mm



Company name:

Created by:

Phone:

Date:

23/12/2025

Qty.	Description
1	Electrical data: Motor type: MSE3 Power input - P1: 1.55 kW Rated power - P2: 1.15 kW Power (P2) required by pump: 1.13 kW Mains frequency: 50 Hz Rated voltage: 1 x 200-240 V Rated current: 8.4 A Power factor: 1.00 Rated speed: 10700 rpm Start. method: direct-on-line Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 1.5 m Motor No: 96160855 Others: Net weight: 5.14 kg Gross weight: 5.86 kg Shipping volume: 0.01 m³ Danish VVS No.: 388442485 Swedish RSK No.: 5853372 Finnish LVI No.: 4762532 Norwegian NRF no.: 9041353 Country of origin: MX Custom tariff no.: 84137029