

D6000 Swing Gates

**INDUSTRIAL
DOOR SERVICES**

SPECIFICATION

MAXIMUM SPAN

14M (7m per leaf)

MAXIMUM HEIGHT

5.0m (Depending on span)

CONSTRUCTION

Up to 4.0m leaf - 80 x 80 Box section, Up to 7.0m leaf - 100 x 100 Box section

POSTS

From 120mm to 250mm box section, depending on gate leaf dimensions

OPENING/CLOSING TIME

6 - 20 seconds (Adjustable)

DRIVE CHOICES

D350v Underground drives for leaves up to 5.0m
D380HD Above ground drives for leaves up to 6.0m
Hydraulic rams for leaves up to 4.5m

SAFETY

Cat 3 Edges as standard with Dual Photocells and a flashing beacon/sounder

CYCLES

100 % Duty Cycle

POWER SUPPLY

230vac 50hz 6Amp



HEAVY DUTY BEARING HINGES

High load bearing equipped hinges are fitted which rotate on the pivot point to minimise closing up of the gate leaf to the post, and so enhancing safety.




FIXING OPTIONS

Gates can be supplied with dig-in or bolt down posts.



AUTOMATION OPTIONS

A range of drive options is available including hydraulic rams, underground drives and heavy duty above ground drive units.



FINISH

Swing gates are powder coated in any standard RAL colour at no additional charge.

TWIN PHOTOCELLS

Safety first. All our powered gates are equipped with class leading safety systems as standard. For the D6000, this includes 6 x Cat. 3 safety edges, twin photocells at different heights, a cabinet mounted Emergency Stop button and a flashing beacon/ sounder. Working with our unique control software this provides the quickest response to a safety event in the industry.



Email: enquiries@indoorserv.co.uk

Telephone: 01633 853335